

Electrolux Super "S" Washers 200 G-force Coin/Card

Save up to 30% on water – automatically. They can even talk and text message you!

Electrolux Professional 200 G-Force high-speed extraction washers minimize drying time and provide significant electrical and gas savings. Self-service laundries benefit from faster throughput (freeing up dryers, folding tables and parking spots) which creates higher profits. Your customers can even receive a text message (option) notifying them when their wash is done and ready for unloading! Increase your profits and create customers for life with the unique features of Electrolux Professional washers.

Features and Benefits:

- AWS Automatic Water Savings:
 Save up to 30% on water with AWS, automatically. With every wash cycle,
 AWS determines the actual weight of the load and adds precisely the right amount of water significantly reducing water consumption and energy costs
- Extremely low water and energy consumption
- Convenient four compartment detergent box
- Larger and more secure coin box
- USB in coin box for easy access and programming
- · High extraction force removes more water, saving energy & time in dryer
- Heavy-duty construction with robust steel door and lock, hinges set wide apart and door locked through entire wash cycle
- Stainless and galvanized steel in all vital parts for maximum rust protection
- SuperBalance guarantees the correct extraction force, longer machine life
- Sanitizing Rinse for greater customer satisfaction and additional revenue
- Single phase electrical for easy installation & lower costs
- Stainless steel front panel
- Drain pump
- Text messaging option
- Voice guidance option

Compass Pro microprocessor offers:

- Large display and one control knob for easy program selection
- More than 20 languages available
- · Real time clock for time of day pricing, happy hour pricing and promotions
- Revenue generating quick selection and option buttons for the most frequently used wash programs and options
- Detailed user statistics and programmability



Available in 20, 25, 30, 45, 62 & 77 lb. capacities. Vertical blue wave front panel standard. Stainless available. Most sizes available in 220 or 120 volt, single phase.

Electrolux models are designed to save water and energy and achieve impressive Modified Energy Factor (MEF) results.















Designed by experts. Inspired by you.

Electrolux S-Series Models	W585S		W5105S		W5130S		W5180S		W5250S		W5330S	
Capacity (lb/kg)	20	9	25	11	30	14	45	20	62	28	77	35
Width (in/mm)	26	660	28 3/8	720	28 3/8	720	29 1/2	750	32 11/16	830	35 13/16	910
Depth (overall) (in/mm)	30 1/8	765	29 1/8	740	32 1/2	825	36	915	39	990	42 5/16	1075
Height (in/mm)	43 7/8	1115	47 1/4	1200	47 1/4	1200	52 3/16	1325	55 1/2	1410	56 7/8	1445
Height to bottom of door (in/mm)	14	355	14 3/8	365	14 3/8	365	17 1/8	435	18 1/2	470	19 11/16	500
Door opening diameter (in/mm)	12 3/16	310	14 3/8	365	15 9/16	395	15 9/16	395	17 1/8	435	17 1/8	435
Cylinder volume (ft3/l)	3	85	3.7	105	4.6	130	6.4	180	8.8	250	11.7	330
Cylinder diameter (in/mm)	20 1/2	520	23 7/16	595	23 7/16	595	25 9/16	650	28 9/16	725	31 5/16	795
Drain outlet diameter (in/mm)	3	75	3	75	3	75	3	75	3	75	3	75
Height to centerline of drain (in/mm)	3 15/16	100	3 15/16	100	3 15/16	100	3 15/16	100	3 15/16	100	3 15/16	100
Height to electrical connection (in/mm)	32 1/2	825	35 13/16	910	35 13/16	910	40 3/4	1035	44 1/8	1120	45 1/2	1155
Height to water connections (in/mm) (approx)	40 9/16	1030	43 7/8	1115	43 7/8	1115	49	1245	52 3/8	1330	53 3/4	1365
Dynamic load (lb/kN)	382+/-742	1.7+/-3.3	472+/-899	2.1+/-4.0	517+/-1057	2.3+/-4.7	2.3+/-4.7	2.7+/-5.9	832+/-1664	3.7+/-7.4	994+/-1978	4.2+/-8.8
Dynamic frequency (Hz)	11.6		10.8		10.8		10.3		9.8		9.4	
Noise level (dBA)	66		71		71		76		79		77	
Net wt (lb/kg)	298	135	385	175	386	175	503	228	633	287	675	306
Crated weight (lb/kg)	344	156	431	196	432	196	529	240	666	302	719	328
Operating Speeds												
Wash (rpm)	52		46		46		44		42		40	
Extract (rpm/G-Force)	830 / 220		776 / 200		776 / 200		742 / 200		702 / 200		641 / 200	
Electrical Requirements (standard)												
Voltage/frequency/phase	208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1-3 phase		208-240/60/1-3 phase	
Full-load current (Amps) / Ckt breaker (Amps)	3.5 / 15		3.8/15		3.8 / 15		5/15		6.9 / 15		9/15	
Voltage/frequency/phase	120/60/1		120/60/1		120/60/1		120/60/1		120/60/1		-	
Full-load current (Amps) / Ckt breaker (Amps)	7/15		7.6 / 15		7.6 / 15		9.5 / 15		13.2 / 20		-	
Water Information												
Inlet fittings (* = 3 inlets)	3/4	DN20	3/4	DN20	3/4	DN20	3/4*	DN20*	3/4*	DN20*	3/4*	DN20*
Flow (gpm/lpm @ 45 psi) (each inlet)	5	20	5	20	5	20	5	20	16	60	16	60
Recommended water pressure (psi/kPa)	30-90	200-600	30-90	200-600	30-90	150-400	30-90	150-400	30-90	150-400	30-90	150-400

Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact us for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.



Electrolux Professional Line 5000 The all-in-one business solution for your self-service laundry.



Greatest flexibility with Compass Pro®

- Real-time clock for time of day pricing, happy hour pricing
- Multi-language menu selection
- Text & voice guidance options
- Easy to program, easy to use



Extended lifetime with Super Balance™

- Less maintenance costs
- Less vibration
- Maximum water extraction
- Lower energy costs



Cost savings in water and energy

with Automatic Water Savings (AWS)

- Determines load weight and adds precisely the correct amount of water
- Up to 30% water savings automatically
- Less water to heat
- Reduces water and energy consumption











Please contact your local authorized Electrolux Professional Distributor.

For Electrolux Professional Laundry Solutions in North America:

Laundrylux 800.381.7222 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338 516-371-4400 • F 516-371-4204 • sales@laundrylux.com Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com Tech Support: 516-371-0700 • F 516-371-4029 • service@laundrylux.com En Mexico: Llame gratis a este numero 001-800-010-1010