

Wascomat W-Series 100G Coin/Card Washers

Dial-in to profitability with reliable 100 G-force Wascomat washers with Compass Control.

Wascomat's W-series washers combine world-class reliability with innovative features and programmability. Featuring 100 G-force extraction and Compass Control, Wascomat washers increase your profits, lower utility costs, and eliminate laundry headaches. We make it affordable and easy to upgrade your laundry!



Available in 20, 25, 30, 45, 62 and 77 lb. capacities. Stainless or white front panels.



Compass Control puts you in control of your laundry operations. One knob does it all!

Wascomat's 100 G-force washers with Compass Control continue our tradition of excellence in technology, design, and quality:

- Lowest water consumption in the industry. Control important functions such as exact water levels, wash times and number of rinses—with a simple turn of a dial.
- Single phase simplicity in 120 or 220 volt.
- Inverter driven motor for smooth and quiet operation, and high efficiency.
- Soft-grip, slip-lock door handle for trouble-free operation. Durable in any environment.
- Door unlocks immediately at the end of final cycle. Wascomat washers are the only machines that have instant door open and close. No delays.
- Unique 4-compartment supply dispenser lets the customer (or attendant) conveniently load all laundry supplies before starting the wash.
- Riveted unibody steel construction eliminates welds for strength and durability.
- Outstanding coin vault security.
- Interchangeable parts from one machine size to another.

Features and benefits:

Wascomat's Compass Control provides the ultimate in flexibility:

- Customize wash programs to lower costs, and meet customer demands.
- Five built-in programs and the capability to easily add or delete programs.
- Create fully customized programs for your specific market using Wash Program Manager.
- Heavy Soil and Extra Rinse options increase store revenue and customer satisfaction.
- Display wash program information in two languages simultaneously.
- Value pricing. Set different prices for different wash programs and option keys.
- Use optional X-10 promotion-pricing system to set discounts for different days and hours each week on specific machines.

Environmentally responsible.

With more than a century of experience behind every machine, Wascomat's state-of-the-art products are engineered for quality, energy savings, and water efficiency. Production units are certified in accordance with ISO 9001 (Quality) and ISO 14001 (Environmental Management) standards, and products are CE and S-labeled. When you buy Wascomat, you are truly investing in the future of your business.

Most sizes available in 220 or 120 volt, single phase!

- Now it's easy to replace top loaders with new front loaders!
- New 5 year warranty!

Wascomat Laundry Equipment

1-800-645-2204 • www.wascomat.com

Wascomat — when laundry means business.

W-Series Models	W620cc		W625cc		W630cc		W645cc		W662cc		W677cc	
Capacity (lb/kg)	20	9	25	11	30	14	45	20	62	28	77	35
Width (in/mm)	26	660	28 3/8	720	28 3/8	720	29 1/2	750	32 11/16	830	35 13/16	910
Depth (overall) (in/mm)	30 1/8	765	29 1/8	740	32 1/2	825	36	915	39	990	42 5/16	1075
Height (in/mm)	43 7/8	1115	47 1/4	1200	47 1/4	1200	52 3/16	1325	55 1/2	1410	56 7/8	1445
Crated width - (in/mm)	27 3/16	690	29 1/2	750	29 1/2	750	30 11/16	780	33 7/8	860	37	940
Crated depth - (in/mm)	32 11/16	830	35 1/16	890	37 3/8	950	39 3/16	995	43 11/16	1110	47 1/16	1195
Crated height - (in/mm)	48	1219	53 1/8	1350	53 1/8	1350	56 7/16	1434	61 1/4	1556	62 7/16	1586
Height to bottom of door (in/mm)	14	355	14 3/8	365	14 3/8	365	17 1/8	435	18 1/2	470	19 11/16	500
Door opening diameter (in/mm)	12 3/16	310	14 3/8	365	15 9/16	395	15 9/16	395	17 1/8	435	17 1/8	435
Cylinder volume (ft ³ /l)	3.0	85	3.7	105	4.6	130	6.4	180	8.8	250	11.7	330
Cylinder diameter (in/mm)	20 1/2	520	23 7/16	595	23 7/16	595	25 9/16	650	28 9/16	725	31 5/16	795
Cylinder depth (in/mm)	16 5/16	414	17 11/16	450	18 7/16	468	21 5/16	542	23 7/8	606	26 3/16	665
Drain outlet diameter (in/mm)	3	75	3	75	3	75	3	75	3	75	3	75
Height to centerline of drain (in/mm)	3 15/16	100	3 15/16	100	3 15/16	100	3 15/16	100	3 15/16	100	3 15/16	100
Height to electrical connection (in/mm)	32 1/2	825	35 13/16	910	35 13/16	910	40 3/4	1035	44 1/8	1120	45 1/2	1155
Height to water connections (in/mm) (approx)	40 9/16	1030	43 7/8	1115	43 7/8	1115	49	1245	52 3/8	1330	53 3/4	1365
Dynamic load (lb/kN)	375+/-696	1.7+/-3.1	468+/-813	2.1+/-3.6	518+/-912	2.3+/-4.1	611+/-1057	2.9+/-4.7	842+/-1189	3.7+/-5.3	1019+/-1310	4.5+/-5.8
Dynamic frequency (Hz)	9.3		8.7		8.7		8.3		7.9		7.5	
Noise level (dBA)	65		71		71		76		79		77	
Net wt (lb/kg)	299	136	374	170	385	175	502	228	631	287	656	298
Crated weight (lb/kg)	330	150	403	183	431	196	528	240	664	302	700	318
Operating Speeds												
Wash (rpm)	52		46		46		44		42		40	
Extract (rpm/G-Force)	587 / 100		548 / 100		548 / 100		525 / 100		497 / 100		474 / 100	
Electrical Requirements (standard)												
Voltage/frequency/phase	208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1	
Full-load current (Amps) / Ckt breaker (Amps)	3.5 / 15		3.8 / 15		3.8 / 15		5 / 15		6.9 / 15		9 / 15	
Voltage/frequency/phase	120/60/1		120/60/1		120/60/1		120/60/1		120/60/1		-	
Full-load current (Amps) / Ckt breaker (Amps)	7 / 15		7.6 / 15		7.6 / 15		9.5 / 15		13.2 / 20		-	
Water Information												
Inlet fittings (* = 3 inlets)	3/4	DN20	3/4	DN20	3/4	DN20	3/4*	DN20*	3/4*	DN20*	3/4*	DN20*
Flow (gpm/lpm @ 45 psi) (each inlet)	5	20	5	20	5	20	5	20	16	60	16	60
Recommended water pressure (psi/kPa)	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600

Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact Laundrylux for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.

SUPERIOR WASH CYCLE CONTROL

With our Wash Program Manager software you can easily create custom wash programs on your PC.



Compass Control

With multilingual Compass Control you choose the programs that best suit your needs. Modify standard wash programs to find the perfect balance between low water and energy consumption—or create your own programs to meet the specific needs of your market. Easily program a higher price for hot washes, extra rinse and heavy soil. Program in discount prices for slow periods of the day or week.

Call today for information on the full line of Wascomat washers, dryers, flatwork ironers and low-cost financing and leasing.

Wascomat Laundry Equipment

1-800-645-2204 • www.wascomat.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338

Sales and Administration – Tel: 516-371-4400 • Fax: 516-371-4204 • e-mail: sales@laundrylux.com

Spare Parts – Tel: 516-371-2000 • Fax: 516-371-4029 • e-mail: parts@laundrylux.com

Technical Support – Tel: 516-371-0700 • Fax: 516-371-4029 • e-mail: service@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010

096201 9.8.10



Your local independent authorized dealer

