

Wascomat Stack & Single Pocket TD Dryers

Wascomat dryers offer reliability, durability, and significant energy savings for self-service laundries.

Wascomat commercial TD dryer models are precision-engineered for efficiency, ease of use, and superior drying results. Our single pocket dryers now have easy to use Compass Pro control. Wascomat dryers are your best choice for reliability, durability, and customer satisfaction. Perfect for coin/card laundries, customers love the fast drying and user-friendly controls.



30x30, 45x45, 35, 67 and 83 lb. capacities. Available in stainless or white front panel. Choice of cash card ready system or drop coin.

Features and benefits:

- Optimal combination of gas consumption (Btu/hr) and airflow (CFM) provides the fastest drying with lowest energy consumption.
- Extra large doors make loading and unloading easy.
- Convenient access to parts.
- Self-cleaning lint screen and large lint compartment for easy maintenance.
- Quiet operation. Our dryers are designed to keep noise level below 70 dB (A).
- Reverse drum operation (option) minimizes tangling and wrinkling, and improves dryer efficiency.

Single Pocket Dryer features:

- **Axial airflow** and tight construction for extremely low energy consumption
- **Compass Pro** program control
- Top Exhaust Kit (optional)

Excellence in every detail.

- Sturdy drum suspension with double-sealed bearings and belt drive.
- Maintenance is minimized with the large lint filter. Lint can easily be removed from the bottom of the compartment.
- Galvanized panels and powder painted exterior protects against rust and corrosion.
- Support rollers for increased drum stability and noise reduction.
- The large door opens nearly 180 degrees and can be hinged to the left or right (on single pocket dryers) for optimal laundry flow. *(Note: On stack dryers - hinge to left must be factory ordered and minimum ordering quantities may apply.)*
- User-friendly, accurate, and flexible dryer control.

 **Wascomat**

1-800-645-2204 • www.laundrylux.com

Wascomat — when laundry means business.

Wascomat Dryer Models	TD30x30		TD45x45		TD35		TD67		TD83	
Capacity (lb/kg)	2 x 30	2 x 13.5	2 x 45	2 x 20.41	35	16.1	67	30.5	83	37.5
Width (in/mm)	31 1/8	790	34 1/4	870	27 15/16	710	37 13/16	960	37 13/16	960
Depth - Gas Models (in/mm)	43 11/16	1110	52 5/8	1336	45 1/2	1155	51 3/4	1315	59 7/16	1510
Depth with door open (in/mm)	72 7/16	1840	85 5/8	2175	68 5/16	1735	83 11/16	2125	91 5/16	2320
Height Overall (in/mm)	76 3/8	1940	81 7/8	2078	65 15/16	1675	73 7/16	1855	73 7/16	1855
Door opening diameter (in/mm)	22 7/8	580	27	686	22 13/16	580	31 7/8	810	31 7/8	810
Cylinder volume (ft ³ /l)	10.6	300	14.6	414	10.2	290	19.4	550	23.8	675
Crated Weight (lb/kg)	693	315	865	392	518	235	717	325	827	375
Utility Connections			(2) 8" or (1) 10"							
Exhaust duct diameter (in/mm)	8	200	(2) 203mm or (1) 254mm		8	200	10	250	10	250
Gas connection	1/2 NPT		3/4 MNPT		1/2 NPT		1/2 NPT		1/2 NPT	
Energy Data										
Gas (Btu/hr)	2 x 71,700		2 X 94,000		71,700		112,700		143,400	
Airflow (ft ³ /min / m ³ /hr) (gas heat)	2 x 354	2 x 600	2 x 600	2 x 1020	360 / 610		550 / 940		670 / 1140	
Electric (kW) @ 208-240V/3Ø	2 x 18	n/a	18	30	13.5 or 18		24 or 32		24 or 32	
Airflow (ft ³ /min / m ³ /hr) (elec. heat)	2 x 354	2 x 600	n/a		325 / 550		550 / 940		670 / 1140	
Electrical Requirements										
Current, gas, 120 V/60Hz (full load/circuit breaker)	2 x 9A / 2 x 15A		2 x 12A / 2 x 15A		7.5A (15A)		12A (20A)		12A (20A)	
Current, gas, 220-240 V/60Hz/1Ø (full load/circuit breaker)	2 x 4.5A / 2 x 15A		5.50A / 15A		3.5A (15A)		8.5A (15A)		8.5A (15A)	
Current, gas, 208-240 V/60Hz/3Ø (full load/circuit breaker)	n/a		n/a		3.75A (15A)		10A (15A)		10A (15A)	
Current, electric, 208-240 V/60Hz/3Ø (full load/circuit breaker)	2 x 50 / 2 x 65		n/a		14.4-18.9 (60A)		26.1-34.4 (110A)		26.1-34.4 (110A)	
Alternate Voltages										
Alternate voltages available. Contact Laundrylux Sales Department for information.										
Supply Pressures										
Natural Gas (inches H.0/mbar)	6 - 10	15 - 25	6 - 12	15 - 30	3.5-10.5 / 9-26		3.5-10.5 / 9-26		3.5-10.5 / 9-26	
Propane (inches H.0/mbar)	10 - 13	25 - 30	11 - 13	28 - 33	8-13	20-32	8-13	20-32	8-13	20-32
Exhaust back pressure (inches H.0/mbar) (max)	1.57	3.9	0.6	1.5	2.2	5.5	2.6	6.48	3	7.5

Note: TD45x45 45 lb. stack dryer - 208 volt, 1-phase not available. Use 120 volt model for 208 volt applications.

Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, inverse-time, common-trip, industrial-type circuit breakers ONLY. Warranty void if not properly installed. Advise when placing order if dryers are for installation at altitudes in excess of 1000 feet above sea level, as this may require a gas-orifice change. Contact Laundrylux for more information and availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.

TD DRYER CONTROLS

Compass PRO available on single pocket Wascomat dryers • Selecta II on 30x30 Stack and 45x45 Stack dryers.



Compass Pro

- Easy program selection
- Easy access with user-friendly interface
- Language selection
- Service program for adjustment of parameters
- USB Type B connection

Selecta II Coin / Card

- 4 temperature settings.
- Displays remaining drying time.
- Coin, token, debit card compatible.
- Complete diagnostics and service mode.



TD45x45 is CSA certified. Other TD dryers are ETL certified.

Call today for information on the full line of Wascomat commercial laundry equipment and low-cost financing and leasing.

Wascomat

1-800-645-2204 • www.laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338

Sales and Administration – Tel: 516-371-4400 • Fax: 516-371-4204 • e-mail: sales@laundrylux.com

Spare Parts – Tel: 516-371-2000 • Fax: 516-371-4029 • e-mail: parts@laundrylux.com

Technical Support – Tel: 516-371-0700 • Fax: 516-371-4029 • e-mail: service@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010

Your local independent authorized dealer

